

# D-TAIL LAB - TECHNICAL DATA SHEET (TDS)

PRODIGY — Hybrid SiO<sub>2</sub> Wet Coat Sealant (HI-CON Series)

Document code: TDS-DPRO • Date: 2025-11-13

Quick Facts		
Product Name	PRODIGY — Hybrid SiO₂ Wet Coat Sealant	
Series	HI-CON	
Color	Clear	
Scent	Characteristic	
pH (25°C)	~6-7 (neutral)	
Mobile Wash Friendly	No	

### Description & Key Benefits

Hybrid  $SiO_2$  + polymer protection to spray on and rinse off — fast, glossy and hydrophobic protection in minutes. Ideal as a wet-coat after a proper wash; also usable on a clean dry panel for targeted boosts.

### Suitable / Do Not Use / Limitations

Suitable: clear-coated paint, gloss plastics/exterior trims, exterior glass (light application), wheels (cool).

Do Not Use: on hot panels or in direct sun: do not let dry before rinsing/buffing

Do Not ose. Of flot patiers of ill direct suit, do not let dry before fillsii	ig/builling.
Limitations: always test sensitive trims; maintain with a pH-neutral sh	nampoo.

Dilution Chart		
Wet-coat dilution	1:20 to 1:50	
Dry-panel method	Use neat on applicator (1-2 sprays)	

#### Directions for Use

Work on a cool, freshly washed and wet vehicle.

Spray evenly on wet panels; immediately rinse with a pressure washer to activate and level; dry with microfiber. Alternative: on a clean dry panel, apply to an applicator, spread a small section, and buff off immediately.

Safety (Summary) — See SDS for full details		
GHS Word	Warning	
Hazards	Causes skin and eye irritation; harmful if swallowed.	
Precautions	Wear gloves/eye protection. Use outdoors or in well-ventilated area.	
First Aid	Skin/Eyes: rinse with water. If swallowed: rinse mouth and seek advice. See SDS §§2/4.	

Transport (Summary)		
UN / Proper Shipping Name	Not regulated as dangerous goods	
Class / Packing Group	_	
TDG / DOT / IMDG / IATA	Not regulated	
Marine Pollutant	No	

# Environmental / Disposal

Avoid release to the environment.

Dispose of contents/container according to local regulations.

## Storage & Shelf Life

Store tightly closed in original container; protect from heat/freezing. Shelf life is stated as 24 months (unopened) when stored as directed.

Packaging & Item Numbers			
Size	SKU	Case Pack	
500 mL	DPRO500	6	

 $\label{lem:manufacturer: D-TAIL LAB | Address: 200 Saint-Francois-Xavier, Unit 114D, Delson, QC | Phone: +1 514-931-4422 | Email: info@dtaillab.com | Site: dtaillab.com • See SDS for full details$