



D-TAIL LAB – TECHNICAL DATA SHEET (TDS)

QUICX — Ceramic Detailing Spray Sealant (SiO₂)

Document code: TDS-DQUX • Date: 2025-11-13

Quick Facts	
Product Name	QUICX — Ceramic Detailing Spray Sealant
Series	—
Color	Yellow
Scent	Fruity
pH (25°C)	7.0-8.0
Mobile Wash Friendly	Yes

Description & Key Benefits

Ready-to-use SiO₂ spray sealant that adds slick gloss and hydrophobics in minutes—standalone or as a topper. Ideal for maintenance after washes; compatible with coatings and traditional sealants.

Suitable / Do Not Use / Limitations

Suitable: clear-coated paint, glossy trims/plastics, wheels (cool), exterior glass (light application).

Do Not Use: on hot panels or under direct sun; do not let dry before buffing.

Limitations: test on sensitive trims; keep towels clean to avoid streaks.

Dilution Chart	
Application	Ready-to-use (do not dilute)

Directions for Use

Wash and dry the vehicle. Mist lightly on a panel or towel, spread, then buff to high gloss.

For best durability, apply two thin coats 12-24 h apart on a decontaminated surface.

Safety (Summary) — See SDS for full details	
GHS Word	Warning
Hazards	Causes skin and eye irritation. Harmful if swallowed.
Precautions	Wear gloves/eye protection. Avoid release to the environment.
First Aid	Skin/Eyes: rinse with water. If swallowed: rinse mouth and call a Poison Center. See SDS §§2/4.

Transport (Summary)	
UN / Proper Shipping Name	Not regulated as dangerous goods
Class / Packing Group	—
TDG / DOT / IMDG / IATA	Not regulated
Marine Pollutant	No

Environmental / Disposal

Avoid release to the environment.

Dispose of contents/container according to local regulations.

Storage & Shelf Life

Store tightly closed; protect from heat/freezing.

Shelf life: 24 months (unopened) when stored as directed.

Packaging & Item Numbers		
Size	SKU	Case Pack
500 mL	DQUX500	6
4 L	DQUX4LT	4
20 L	DQUX20L	

Manufacturer: D-TAIL LAB | Address: 200 Saint-Francois-Xavier, Unit 114D, Delson, QC | Phone: +1 514-931-4422 | Email: info@dtailab.com | Site: dtailab.com • See SDS for full details