



D-TAIL LAB - TECHNICAL DATA SHEET (TDS)

DWAX — Hydrophobic Liquid Wax (RTU)

Document code: TDS-DWAX • Date: 2025-11-16

Quick Facts

Product Code / SKUs	DWAX500 (500 mL); DWAX4LT (4 L); DWAX20L (20 L)
Product Type	Sprayable hydrophobic liquid wax — Ready-To-Use (RTU)
Intended Use	Fast gloss & water repellency on exterior paint and glossy trims
Appearance / Color	Orange
Odor / Scent	Fruity
Base	Water-based; non-flammable
pH (as supplied)	7.0-8.0 (near-neutral)
Specific Gravity (20 °C)	See SDS — Section 9
VOC (approx.)	≈ 3% (from product page)

Description & Key Benefits

Sprayable liquid wax that lays down a super-hydrophobic layer to boost beading, slickness, and gloss. Use on wet panels as a rinse-aid or on dry paint as a wipe-on, wipe-off wax.

- Quick, glossy protection in minutes
- Super hydrophobic beading helps panels dry faster
- UV help to reduce oxidation and color fade
- Use wet (spray-on/rinse-off) or dry (wipe-on/wipe-off)

Suitable Surfaces / Materials

Clear-coated paint and painted plastics, gloss exterior trims, door jambs.

Do Not Use On / Limitations

Avoid hot panels/direct sun. Do not allow to dry on surface when using wet method. Spot-test sensitive trims.

Dilution Chart

Task	Dilution (Product:Water)	Notes
All uses	RTU — do not dilute	Wet: spray on, rinse, then dry. Dry: spray or pad-apply, then buff.

Directions for Use

Work on a cool, clean surface. Wet method: after washing, leave panels wet, spray DWAX uniformly, then rinse immediately (pressure washer ideal). Dry afterward. Dry method: spray lightly on paint or an applicator, spread, then gently buff with a clean microfiber until streak-free.

Safety (Summary) — See SDS for full details

GHS Signal Word	Warning
Primary Hazards (H-statements)	Acute Oral Tox. Cat. 4; Skin Irrit. Cat. 2; Eye Irrit. Cat. 2B.
Primary Precautions (P-statements)	Wear gloves and eye protection. Do not eat, drink or smoke when using. Wash thoroughly after handling.
First Aid (summary)	If swallowed: call a poison centre/doctor; rinse mouth. Eyes: rinse cautiously 15 min. Skin: wash with water. Inhalation: fresh air.

Transport (Summary)

UN / Proper Shipping Name	See SDS — Section 14
Class / Packing Group	See SDS — Section 14
TDG / DOT / IMDG / IATA	See SDS — Section 14
Marine Pollutant	See SDS — Section 14

Environmental / Disposal

Avoid release to environment. Dispose of contents/container per local/regional regulations.

Storage & Shelf Life

Store tightly closed, away from incompatible materials (strong oxidizers). Protect from extreme temperatures.

Packaging & Item Numbers

Size	Item No. / SKU	Case Pack
500 mL	DWAX500	6
4 L	DWAX4LT	4
20 L	DWAX20L	

Manufacturer: D-TAIL LAB | 200 Saint-Francois-Xavier, Unit 114D, Delson, QC | +1 514-931-4422 | info@dtailab.com | dtailab.com

SDS: see latest version linked on the DWAX product page at dtailab.com